

		Model	EW 900R	
		Code Production	TT3923REWNCDD +RC	
		Interface :		
				
				
	Overall Dimension (Width-Depth-Height) *open	mm	788 - 835 - 2265	
	Packaging Dimension (WxDxH) +(additional RC package)	mm	870x830x1540+(800x750x300)	
	Gross weight +(RC)	Kg	130 +(25)	
	Net weight +(RC)	Kg	120 +(23)	
	Volume +(RC)	mc	1,10 +(0,15)	
	Rack size	mm	500x600	
	Max door /hood opening	mm	465	
	Max glasses/plate Height	mm	440	
	General construction		double skin	
	Door/hood Construction		double skin	
	Tank construction		deep drawn	
	Tank volume	liter	30	
	Tank heating element	W	3.000	
	Tank surface strainers		Yes-composite	
	Wash pump type		double flow	
	Wash pump power	W	1.500	
	Wash temperature	°C	60	
	Boiler type		without pressure	
	Boiler volume	liter	12	
	Back-flow system		break tank	
	Boiler heating element	W	8.000	
	Rinse booster pump		YES	
	Rinse booster pump power	W	200	
	Rinse temperature	°C	80	
	Rinse water consumption	Liter /rack	3	
	Optimal external water pressure	bar	1 - 4	
	Drain system		deep drain	
	Drain filter		double filter	
	Drain pump		YES	
	Rinse aid dispenser	peristaltic	YES	
	Detergent dispenser	peristaltic	YES	
	Wash cycle	sec	60 - 90 - 150 - continuous	
	Self cleaning cycle		YES	
	Water softener (type continuous)		NO	
	Heat recovery fan	W	50	
	Heat recovery air flow	m³/h	680	
	Residual heat emission SENSITIVE	KW	0,6	
	Residual heat emission LATENT	KW	0,6	
	Electric Power	W	9.500	
	Electric Connection	V - ph - Hz	400V 3N 50Hz	
	Fuse	A	16	
	Plates racks	n° 1	70180	
	Flat Rack	n° 1	70181	
	Cutterly Rack	n° 1	780081	

Electric cable	n° 1	YES
Drain hose	n° 1	YES
Fill hose "WaterMark"	n° 1	YES

